


LED2 HIGH BAY SM 120W DALI EM 3h.



Name	
Code	
Color	
Category	
Power	
Lumen output	
Color temperature	
Efficacy	
Driver	
Electrical insulation class	
Voltage/frequency	


Color Rendering Index	
SDCM	
Light beam angle	
Unified Glare Rating	
Light source	
Dimmable	
LED Lifetime	
Warranty	

Ingress Protection	
Material	

Product

LED2 HIGH BAY SM 120W DALI EM 3h
6359441D EM 3h
BLACK
PROFI

Power

120 W ± 10 %
18000 lm ± 10 %
4000K
150 lm/W
3300 mA
 220-240V/50-60Hz

Information

80+
< 3
120°
N/A
LED
DALI
L80 80.000h L70 127.000h -30°C +50°C
5 YEAR

Other data

IP65
ALU Alloy + PC cover

SK

Použitie:
obchodné priestory, sklady, výrobné priestory

SMART-READY

Center-hollow design for fast installation of sensor or wireless control module.
Ready for further **dynamic energy saving**.

FINISH

Five-step, super durable TGIC paint material help resist **all tough environments** conditions while providing optimal color maintenance.

OPTICS

Available with 3 types of fine-designed PC lens features low glare with **UGR<19** for some models.

CONSTRUCTION

Aluminum alloy made heatsink features hollow fins to optimize thermal management which also result in **less dust accumulation and light weight**.