



# ROUND II



Round surface light fitting for interior or exterior mounting in IP54, equipped with SMD LEDs. Possibility to change light temperature by switch during installation. Available in 3 different sizes with direct diffused lighting effect. Housing and diffuser made of polycarbonate. Available in white color.

Application: general lighting, intended for residential or commercial areas in any type of spaces, including humid and dusty environment (bathroom, hallway, stairway, wardrobe).



<b>25</b>	Polycarbonate	White	<b>Ø: 250 mm</b> <b>H: 50 mm</b>	<b>12 W LED</b>	3000K / 4000K / 5700K	<b>1200 lm</b>	> 80	120°	220-240V 50-60Hz	fix	54	<b>0,79 kg</b>
<b>30</b>	Polycarbonate	White	<b>Ø: 300 mm</b> <b>H: 58 mm</b>	<b>25 W LED</b>	3000K / 4000K / 5700K	<b>2200 lm</b>	> 80	120°	220-240V 50-60Hz	fix	54	<b>1,14 kg</b>
<b>40</b>	Polycarbonate	White	<b>Ø: 400 mm</b> <b>H: 63 mm</b>	<b>30 W LED</b>	3000K / 4000K / 5700K	<b>3000 lm</b>	> 80	120°	220-240V 50-60Hz	fix	54	<b>1,9 kg</b>

Material	Color	Dimensions	Light source	Color temperature	Lumens output	CRI	Optics	Mains voltage	Output driver current	IP Rating	Weight
----------	-------	------------	--------------	-------------------	---------------	-----	--------	---------------	-----------------------	-----------	--------