SQUARE II

Square surface light fitting for interior or exterior mounting in IP54, equipped with SMD LEDs. Possibility to change light temperature by switch during installation. Available in 3 different sizes with direct diffused lighting effect. Housing and diffuser made of polycarbonate. Available in white color.

Application: general lighting, intended for residential or commercial areas in any type of spaces, including humid and dusty enviroment (bathroom, hallway, stairway, wardrobe).

	Material	Color	Dimensions	Light source	Color temperature	Lumens output	CRI	Optics	Mains voltage	Output driver current	IP Rating	Weight
25	Polycarbonate	White	**250 x 250 mm H: 50 mm**	**12 W LED**	3000K / 4000K / 5700K	**1200 lm**	> 80	120°	220-240V 50-60Hz	fix	54	**0,9 kg**
30	Polycarbonate	White	**300 x 300 mm H: 58 mm**	**25 W LED**	3000K / 4000K / 5700K	**2200 lm**	> 80	120°	220-240V 50-60Hz	fix	54	**1,26 kg**
40	Polycarbonate	White	**400 x 400 mm H: 63 mm**	**30 W LED**	3000K / 4000K / 5700K	**3000 lm**	> 80	120°	220-240V 50-60Hz	fix	54	**2,08 kg**