



ZETA



Recessed round light fitting for interior mounting with low height, equipped with SMD LEDs. Diffused lighting. Housing made of aluminium, prismatic opal diffuser with low glare index. Available in 4 sizes, white or black color.

Application: general lighting, intended for residential or commercial areas (hallway, offices, entrance areas, general room lighting, working areas).



Size	Material	Color	Dimensions	Recessed hole	Light source	Color temperature	Lumens output	CRI	Optics	Unified Glare Rating	Dimmable	Mains voltage	Output driver current	IP Rating
XS	Aluminium, PMMA	White Black	Ø: 103 mm x 56,5 mm	Ø: 90 mm	7 W	3000 K	650 lm	> 80	90°	< 19	DALI /PUSH	220-240V 50-60Hz	350 mA	44
S	Aluminium, PMMA	White Black	Ø: 136 mm x 56,5 mm	Ø: 120 mm	10 W 15 W	3000 K 4000 K	980 lm 1620 lm	> 80	90°	< 19	DALI /PUSH	220-240V 50-60Hz	250 mA	44
M	Aluminium, PMMA	White Black	Ø: 176 mm x 59,5 mm	Ø: 160 mm	20 W	3000 K 4000 K	2000 lm 2200 lm	> 80	90°	< 19	DALI /PUSH	220-240V 50-60Hz	500 mA	44
L	Aluminium, PMMA	White Black	Ø: 210 mm x 60 mm	Ø: 200 mm	25 W	3000 K	2500 lm	> 80	90°	< 19	DALI /PUSH	220-240V 50-60Hz	600 mA	44